



WWW.HARDESIGNSELECTION.CA
INFO@HARDESIGNSELECTION.CA

HARD HD-C-650 *Design* **PERMANENT**

Decorative concrete sealer

Decorative, permanent and penetrating surface coating, with high density and outstanding resistance to bacteria and humidity while being easy to maintain.

Suggested utilization on counters, as decorative item, on walls, floors (light to medium traffic).

System approved by the Canadian Food Inspection Agency.*

Applicable in one or several layers, according to the desired finish.

Offers excellent adhesion.

Final luster according to your needs :

- **Matte finish**
- **Glossy finish**

3 components epoxide base, **without COV**, allowing an interior application without the strong smell.

Mix :

-Stir well before usage-

- 10 part of "A"
- 2 part of "B"
- 5 part of "C"

Step 1 : mix part "A" with part "B "

Step 2 : incorporate part "C" and mix strongly for 1 minute

Gel time : at 25'C +/- 50 minutes

Cure : +/- 16 hours at 20'C minimum

Complete cure : 7 days

Clean with Acetone

Coverage for :

"A" 100 ml / "B" 20 ml / "C" 50 ml

Total : 170 ml = 50 to 125 square feet according to the application.

For a **matte finish** application use only the half of the quantity to avoid excessive loss, due to a longer application time

System approved by the Canadian Food Inspection Agency *

*Using only part "A" and "C"

Application :

On a Clean and dry surface, polished or not

Matte finish :

The success of a matte finish depend on the application, only a very thin penetrating layer being necessary.

Apply with a microfiber cloth, soak one corner and stretch the more you can the quantity on the surface. The more the product is spread, the easier it will be to wipe afterwards. The product may also be wipe all along the application, in order to facilitate the final wiping. Make sure however that the micro-pores are well-filled in order to avoid unprotected surfaces.

Then proceed to the final wiping, using a new and good quality microfiber cloth. Start wiping the surface until the cloth slide easily on the surface.

The success of a matte finish depends on this step.

A few test to master the technique are suggested.

Note : It is suggested to be 2 for this application on large surface.

Glossy finish :

Apply with a paintbrush, a roller, a gun or pour it on the surface. Apply the product in thin or thick layers, according to the desired result , if the surface is vertical thin layer is suggested. One or several layers may be applied (light sanding between layers).

Note :

It is suggested to make several mixes if the surface is large in order to avoid that the product cure during the application.

GUARANTEE :

The product will retain permanent protection proprieties if applied properly according to our recommendations.

As long as it is not removed by abrasion, wearing or is damaged.

A chipping, stripping or staining finish will result from : either a wrong application, a contaminated surface before application, or after application (from a unsealed section). According to Hardsign inc. (9208-7170 que. inc.), the product respects the above-mentioned qualities in the manual, it has been meticulously tested in a laboratory in order to be as efficient and durable as a surface sealant product.

The purchaser and the user agree that :

Hardsign inc. (9208-7170 que. Inc.) may not be held responsible in any way for the damage or inconveniences related to the use of this product.